

Euroview Fold and Slide Door

Opening Diagrams

3 Sash



Schematic 321

Schematic 330

4 Sash



Schematic 431

5 Sash



Schematic 541

Schematic 550

Schematic 532

6 Sash



Schematic 651

Schematic 633

7 Sash



Schematic 761

Schematic 743



Schematic 770

Depending upon hardware manufacturer different opening types available!

VEKA Inc. has made every effort to ensure that the information contained in this brochure is correct at the time of publication, but cannot be held responsible for any errors or omissions and reserves the right to change designs, specifications and products at any time without prior notice. © VEKA Inc. 2007

VEKA Inc • 100 Veka Drive • Fombell, PA 16123 • Phone 724 452-1000 • Toll Free 800 654-5589 • Fax 724 452-1007 • www.vekainc.com



Euroview Fold and Slide Door

more than good looks





Generous and convenient access

All folding sashes are moved to the side to form a slim package. Living room and garden/patio are united to form a new living area in close touch with nature.



Frequent use:

A side hinged or tilt/turn sash, the passage door, is operated independently of the folding sashes.



Efficient Ventilation:

All 3 to 7 sash units are equipped with an optional Tilt/Turn passage door. In the secured tilt position, this sash offers additional possibility of ventilation.



Bring the Outside Inside with Folding Doors

The Veka Fold and Slide door system offers contemporary style, effective design and excellent reliability. Our Fold and Slide door system provides superior operating performance and smooth integration into any architectural style and space. The door systems are engineered using high quality PVC-Window and Door Profiles and superior hinge and locking systems that are reliable and secure. The rollers along which the doors slide, offer a smooth glide and reliable performance with solid design and expert engineering. Choose from three to seven operating panels in various configurations. The door systems are available in a range of colors including white Et Ivory, woodgrain laminates, such as mahogany, golden oak, montana, marcure and a variety of other solid colors.

- All main profiles shown with galvanized steel reinforcement sections
- Alternative outer frame and sill sizes available
- Thresholds can be standard outer frames or low profile aluminum thresholds to suit different installations, weather and security performance requirements
- Alternative beads available in sloped or sculptured designs
- Glazing beads available for different IG-Sizes 3/4" to 1-1/2"
- Ideal in both residential and commercial applications
- Available inswing or outswing opening
- 70mm front to back multi-chambered profiles
- Available in white, bone, clay, wood grain and colored finishes (laminated)



Horizontal cross section of 3-panel door (inswing)

- The design of the running rail at the sill, transfers the weight of the sashes safely to the floor. As a result, safe functioning is provided, independent from the building construction at the head.
- Folding sashes with a maximum width of 900mm and a weight of 80kg are possible.
- Provided with compression gaskets, the units offer a high air and water infiltration performance, as well as optimal heat and sound insulation.
- Stylish appearance due to a flat guide rail and concealed hardware.
- Fold and Slide doors can be delivered as inward or outward opening units. Applications for 3 to 7 sash units are possible.
- Top running and bottom running units can be delivered depending on hardware manufacturer.
- Zero-Thresholds are available upon request depending on hardware manufacturer.