

The Performer is the ideal solution for coastal applications requiring a DP 50 rating. Thick wall, all-welded vinyl frame and sash combined with a 1" glass package and reinforcing achieves the ratings for stringent codes enforced in coastal regions.

**IMPACT  
RATED**



**BASELINE PERFORMANCE**

Thermal Insulation		
Glass	Uc Value	R Value
Clear	0.47	2.12
LoE/Argon	0.28	3.57
Dual LoE/Argon	0.22	4.55

  

Structural Performance	
Air Infiltration @ 25mph	0.08 cfm/ft²
Water Penetration	7.50 psf
Uniform Loads	+/- 75.00 psf

AAMA RATING: SGC-LC50

**Standard Features**

- Multi-point locking hardware
- All welded frame & sash
- Colors: White, Beige, Clay
- Internal weep system
- Stainless steel adjustable tandem rollers, lock and striker
- Keyed lock cylinder
- New construction nail fin
- Integral J-channel
- Field Reversible
- XO, OX, OXO configurations
- 12 gauge steel reinforcing
- White, beige or clay hardware finish
- Accommodates 1" glazing
- Dual seal weatherstripping
- Exterior glazed
- Integral screen track
- Vinyl threshold cover
- AAMA approved PVC lineal certification
- NFRC simulations

**Optional Features**

- Brass or Satin Nickel hardware
- Sliding screens available as per distributor

